

Why Beltscoop?

Drying with a Beltscoop spreader is fast and easy, while ensuring even spreading of the bedding. Large quantities of straw can be chopped into the bedding storage, thus saving time. Moreover, the shed is spared from fine dust caused by chopping.

The same unit can be used to spread peat from the storage directly into the shed.

Spreading of bedding creates less dust and noise than when a bale chopper is used, where peat/straw is spread by a fan.

A Beltscoop unit makes it possible to use different beddings and their mixtures, which allows to select the method that is the most appropriate and cost-effective in the particular farm.

The small loader models let you spread bedding even in confined spaces.

Buckets can also be used for feeding.

Alasuutari, Sakari. Kuivikkeiden varastointi ja kuivitusmenetelmät. (Bedding storage and drying methods) TTS newsletter: Maataloustyö ja tuottavuus 8/2011 (635). ISSN 1799-5523. Työtehoseura. Oy Fram Ab. Vaasa 2011.

What Beltscoop?

Beltscoop is a bedding spreader manufactured in Finland.

It can be used for spreading beddings such as peat and chips as well as straw chopped with a forage feeder or a bale chopper. The bucket is designed mostly for bedding, but can be also applied to distribution of crushed grain, flour, chopped dry hay, fodder and other pre-chopped products. Hot-dip galvanized buckets are made in a number of different sizes, and are available with all the commonly used loader couplings.

SPEED AND EFFICIENCY

REDUCED PHYSICAL EFFORT

ANIMAL WELFARE

Beltscoop - who for:

The Beltscoop bedding spreader is particularly suited for using in stanchion tied and loose housing systems with inclined straw beds as well as in fur farms.











Beltscoop 500:

capacity 500 I / L1000 mm / weight 260kg Bedding width1-3 metres

Beltscoop 700:

capacity 700 I / L1300 mm / weight 320kg Bedding width 1-3 metres

Beltscoop 1000:

capacity 1000 I / L1500 mm / weight 380kg Bedding width 1-3 metres

Beltscoop 2000:

capacity 2000I / L2000 mm / weight 520kg Bedding width 1-5 metres

Beltscoop 2500:

capacity 2500 I / L2500 mm / weight 700kg Bedding width 1-5 metres

Beltscoop 3000:

capacity 3000 I / L3000 mm / weight 900kg Bedding width 1-5 metres



Beltscoop presentation videos www.ny-tek.fi



Ny-Tek Oy Yritysahontie 5 85900 Reisjärvi FINLAND

sales@nytek.fi





Beltscoop BEDDING SPREADER

Bedding efficiency for loose housing systems and fur farms